



**NOTES:**

1. Sign Blank: 2.0 mm (0.080") aluminum 5052-H38 alloy. Before applying reflective sheeting, clean the blank and apply a chromate conversion coating to the entire surface.
2. Reflective sheeting: super engineer grade. Apply letters and border with a screen process.
3. Lettering: 2 NC Highway Gothic.

Suffix Abbreviations	
Avenue	AV or AVE
Boulevard	BL or BLVD
Circle	CIR
Court	CT
Diagonal	DIAG
Drive	DR
Heights	HTS
Highway	HWY
Lane	LN
Park	PK
Parkway	PKY or PKWY
Place	PL
Plaza	PZ
Road	RD
Street	ST
Terrace	TER
Trail	TR
Turn	TN
Walk	WK
Way	WY or WAY

	Letter Height
Street Name	115 (4.50") UC 90 (3.50") LC
Suffix	50 (2") UC
Block No.	50 (2")

Count of Street Name Characters	Sign Length
5 or fewer	610 (24")
6 or 7	760 (30")
8	915 (36")
9	1065 (42")
10 or more	1220 (48")

Dimensions are in millimeters, except as noted

<b>REVISIONS</b>		<b>CITY OF LONG BEACH, CALIFORNIA</b> DEPARTMENT OF PUBLIC WORKS	STANDARD PLAN NO.
NO.	DATE		
1	06/14/01	<b>STANDARD STREET NAME SIGN</b>	METRIC 319
2	12/23/02		
3	02/28/03		
4		APPROVED BY: <i>Paul A. [Signature]</i> CITY ENGINEER R.E. No. 40599	DATE: 4/16/03 EX. DATE: 03/31/07
			SHEET 1 OF 1