



**NOTES:**

1. Posts shall be structural grade redwood or preservative treated Douglas Fir, surfaced four sides; cross pieces shall be 50 x 300 mm (2" x 12") select grade Douglas Fir, surfaced four sides.
2. All exposed portions of barricades shall be painted with two coats of white exterior enamel over prime coat.
3. Connections shall be made with 10 x 150 mm (3/8" x 6") galvanized lag screws with one (1) washer each. Reflector sign fasteners shall be 10 x 40 mm (3/8" x 1 1/2") galvanized lag screws.
4. Reflector signs shall be Caltrans Type N-2 for use on dead end streets and Type N-1 for all other conditions.
5. Markings for barricade rails shall be reflectorized alternate orange and white stripes in accordance with the "Work Area Traffic Control Handbook."

Dimensions are in millimeters, except as noted

<b>REVISIONS</b>	<b>CITY OF LONG BEACH, CALIFORNIA</b>		<b>STANDARD PLAN NO.</b>
<b>NO. DATE</b>	<b>DEPARTMENT OF PUBLIC WORKS</b>		
1 04/04/96	<b>PERMANENT BARRICADE</b>		<b>METRIC 128</b>
2 12/23/02			<b>SHEET</b>
3			<b>1 OF 1</b>
4			
APPROVED BY: <i>Max Antille</i>		DATE: 1/10/03	
CITY ENGINEER R.E. No. 70599		EX. DATE 03/31/03	